

Spiral "Åleruse" til stavvibrator

Produkt:

Spiral "Åleruse" til stavvibrator.



Anvendelse:

Anvendes for undgå at stavvibratoren kiler sig fast i armeringen. Udvendig diameter fastsættes ud fra størrelse på stavvibrator +40mm til bevægelse.

Længden fastsætter antal omgange. 1 omgang svarer til ca. 100mm udfoldet længde.

Produktet fremstilles efter opgave.

Byggevareidentifikation:

Etiket/følgeseddel angiver produkttype, udv. dimension, antal omgange, trådtykkelse og overflade. Eks. Spiral ø96 mm, 32 omgange ø4,0 mm blank tråd.

Materiale/overflade:

Produceres som standard i Ø4mm rund tråd kvalitet C9D iht. EN16120-2. Kan produceres i andre størrelser og materialer efter behov.

Sporbarhed:

Kan leveres sporbart til 3.1 certifikat iht. DS/EN 10204:2004.

Referencer:

Valsetråd af ulegeret stål til fremstilling af tråd - DS/ISO 16120-2

Spiral "Åleruse" for concrete vibrator

Product:

Spiral "Åleruse" for concrete vibrator



Application:

Used for insuring that the concrete vibrator is not stuck in the reinforcement. Outer diameter is based on the diameter of vibrator. Normaly +40 mm for movement.

Length is defined by number of laps. 1 lap equals approx. 100 mm in unfolded lenght.

The product is manufactured to order.

Construction product identification:

Label/packing list indicates "Spiral", outer dimension, number of laps, wire diameter and surface. Eg. Spiral ø96mm, 32 laps ø4,0mm plain wire.

Material:

As standard manufactured in Ø4mm round wire in quality C9D according to EN16120-2. Other sizes and materials can be manufactured as needed.

Tracebilty:

Can be delivered traceable to 3.1 certificate according to DS/EN 10204:2004.

Referencer:

Non-alloy steel wire rod conversion to wire - DS/ISO 16120-2